

Declaration of Performance

DoP Reference no.: SSL 25 (Rev. 4)

Product type: Box 175, Box 175/K

Intended use:

Structural support for openings in walls and

partitions

Manufacturer:	Notified body:
Steelite Specials Ltd.	Technical & Test Institute for Construction Prague
Cappanargid, Rathangan, Co. Kildare,	Prosecká 811/76a, Prosek, 190 00 Praha 9
Republic of Ireland	Czech Republic
Declares in compliance with the Construction Products Regulation (EU) No. 305/2011, that the referred products are manufactured according to the requirements of the European Harmonised Standard EN 845-2:2013+A1-2016 and fulfil the conditions for CE Marking in accordance with annex ZA of EN 845-2:2013+A1-2016	requirements in Annex ZA.1 and ZA.2 of EN 845-2-2016
	Notified Body Number: 1020
	The AVCP for the product: System 3

Essential characteristics												
Lintel length	mm	600	1650	1950	2250	2550	2850	3250	3750			
		1500	1800	2100	2400	2700	3000	3500	4000			
Safe load bearing capacity	kN	82	65	55	49	45	42	39	38			
Ultimate load bearing capacity	kN	131	104	88	77	72	68	62	60			2016
Deflection under load	Less then effective span / 325 at maximum load											. A1:
Mass per meter length	kg/m 18.8											13 +
Water absorption	Zero											2: 201
Thermal resistance	50 (steel), 0.036 (insulation) W/mK											845-
Resistance to fire	NPD											EN 8
Durability (corrosion)	Material coating reference L14											
Durability (freeze/thaw)	Resistant											
Dangerous substances	None											

Signed for on behalf of the manufacturer by:

Name: Ryan Marshall

Date:

14-Mar-23

Signature: Ryan Marshall

 $C \in$