

Declaration of Performance

DoP Reference no.: SSL 21 (Rev. 5)

Product type: **CL/WIL, CL/WIL/K 140, 150, 160**

Intended use: Structural support for openings in walls and

partitions

Manufacturer:

Steelite Specials Ltd.

Cappanargid, Rathangan, Co. Kildare, Republic of Ireland

Declares in compliance with the Construction Products
Regulation (EU) No. 305/2011, that the referred products
are manufactured according to the requirements of the
European Harmonised Standard EN 845-2:2013+A1-2016
and fulfil the conditions for CE Marking in accordance with
annex ZA of EN 845-2:2013+A1-2016

Technical & Test Institute for Construction Prague
Prosecká 811/76a, Prosek, 190 00 Praha 9
Czech Republic

Notified body:

The conformity of the product was determined as per the requirements in Annex ZA.1 and ZA.2 of EN 845-2-2013+A1-2016

Notified Body Number: 1020

The AVCP for the product: System 3

Essential characteristics												
Lintel length	mm	600	1650	1950	2250	2550	2850	3250	3750	4250	4750	
		1500	1800	2100	2400	2700	3000	3500	4000	4500		
Safe load bearing capacity (Load ratio 1:3)	kN	68	66	56	50	47	44	41	41	40	40	
Ultimate load bearing capacity (Load ratio 1:3)	kN	108	106	90	80	75	70	66	65	64	64	2016
Deflection under load	Less then effective span / 325 at maximum load							Α1				
Mass per meter length	kg/m 34.7 <u>~</u>							13 +				
Water absorption	Zero							2: 20				
Thermal resistance	I 1							845-				
Resistance to fire	NPD Z											
Durability (corrosion)	Material coating reference L14											
Durability (freeze/thaw)	Resistant											
Dangerous substances	None											

Signed for on behalf of the manufacturer by:

Name: Ryan Marshall Signature: Ryan Marshall

Date: 14-Mar-23

