



## Declaration of Performance

DoP Reference no.: SSL 09

Product type: **CL, CL/K 165, 170, 175, 180, 185**

Intended use: Structural support for openings in walls and partitions

Manufacturer:

**Steelite Specials Ltd.**

Cappanargid, Rathangan, Co. Kildare,  
Republic of Ireland

Notified body:

**OMNI Assured Certification International. Ltd NB 2819**

1 Parkgate, Princes Street, Tralee  
Co. Kerry, Ireland

Declares in compliance with the Construction Products Regulation (EU) No. 305/2011, that the referred products are manufactured according to the requirements of the European Harmonised Standard EN 845-2:2013 and fulfil the conditions for CE Marking in accordance with annex ZA of EN 845-2:2013

The conformity of the product was determined as per the requirements in Annex ZA of EN 845-2: Specification for ancillary components for masonry - Part 2.

Certificate Number: OMNi-00149-FPC

The AVCP for the product: **System 3**

### Essential characteristics

Lintel length	mm	600	1650	1950	2250	2550	2850	3250	3750	4250	4750
Safe load bearing capacity (Load ratio 1:3)	kN	120	116	91	75	71	68	63	59	57	56
Ultimate load bearing capacity (Load ratio 1:3)	kN	192	185	145	120	114	109	101	95	90	89
Deflection under load	Less than effective span / 325 at maximum load										
Mass per meter length	kg/m	25.2									
Water absorption	Zero										
Thermal resistance	50 (steel), 0.036 (insulation) W/mK										
Resistance to fire	NPD										
Durability (corrosion)	Material coating reference L14										
Durability (freeze/thaw)	Resistant										
Dangerous substances	None										

EN 845-2: 2013

**Signed for on behalf of the manufacturer by:**

**Name:** Ryan Marshall

**Signature:** Ryan Marshall

**Date:** 10-Oct-19