



Declaration of Performance

DoP Reference no.: SSL 13

Product type: L 26, L 26/K

Intended use: Structural support for openings in walls and partitions

Manufacturer:

Steelite Specials Ltd.
Cappanargid, Rathangan, Co. Kildare,
Republic of Ireland

Notified body:

OMNI Assured Certification International. Ltd NB 2819
1 Parkgate, Princes Street, Tralee
Co. Kerry, Ireland

Declares in compliance with the Construction Products Regulation (EU) No. 305/2011, that the referred products are manufactured according to the requirements of the European Harmonised Standard EN 845-2:2013 and fulfil the conditions for CE Marking in accordance with annex ZA of EN 845-2:2013

The conformity of the product was determined as per the requirements in Annex ZA of EN 845-2: Specification for ancillary components for masonry - Part 2.

Certificate Number: OMNi-00149-FPC

The AVCP for the product: **System 3**

Essential characteristics

Lintel length	mm	600 1200	1350 1650	1800 2100	2250 2400	2550 2700	2850 3000	3250 3500	3750 4000	4250 4500	4750
Safe load bearing capacity	kN	16	14	13	12	6	9	8	8	8	8
Ultimate load bearing capacity	kN	26	23	21	19	10	14	14	13	13	13
Deflection under load	Less then effective span / 325 at maximum load										
Mass per meter length	kg/m	4.6		5.6	7.1			9.4			
Water absorption	Zero										
Thermal resistance	50 (steel) W/mK										
Resistance to fire	NPD										
Durability (corrosion)	Material coating reference L14										
Durability (freeze/thaw)	Resistant										
Dangerous substances	None										

EN 845-2: 2013

Signed for on behalf of the manufacturer by:

Name: Ryan Marshall

Date: 10-Oct-19

Signature: Ryan Marshall