



## Declaration of Performance

DoP Reference no.: SSL 27

Product type: **L 31, L 31/K**

Intended use: Structural support for openings in walls and partitions

Manufacturer:

**Steelite Specials Ltd.**

Cappanargid, Rathangan, Co. Kildare,  
Republic of Ireland

Notified body:

**OMNI Assured Certification International. Ltd NB 2819**

1 Parkgate, Princes Street, Tralee  
Co. Kerry, Ireland

Declares in compliance with the Construction Products Regulation (EU) No. 305/2011, that the referred products are manufactured according to the requirements of the European Harmonised Standard EN 845-2:2013 and fulfil the conditions for CE Marking in accordance with annex ZA of EN 845-2:2013

The conformity of the product was determined as per the requirements in Annex ZA of EN 845-2: Specification for ancillary components for masonry - Part 2.

Certificate Number: OMNi-00149-FPC

The AVCP for the product: **System 3**

### Essential characteristics

<i>Lintel length</i>	mm	600 1050	1200 1350	1500 1650	1800 2100	2250 2400	2550 2700	2850 3000				EN 845-2: 2013
<i>Safe load bearing capacity</i>	kN	11	11	11	10	10	10	10				
<i>Ultimate load bearing capacity</i>	kN	18	18	18	16	16	16	16				
<i>Deflection under load</i>	Less then effective span / 325 at maximum load											
Mass per meter length	kg/m	9.2			11.2	14.2						
Water absorption	Zero											
Thermal resistance	50 (steel) W/mK											
Resistance to fire	NPD											
Durability (corrosion)	Material coating reference L14											
Durability (freeze/thaw)	Resistant											
Dangerous substances	None											

Signed for on behalf of the manufacturer by:

Name: Ryan Marshall

Signature: *Ryan Marshall*

Date: 10-Oct-19