



Declaration of Performance

DoP Reference no.: SSL 16

Product type: **L 38, L 38/K 115, 120, 125, 130, 135**

Intended use: Structural support for openings in walls and partitions

Manufacturer:

Steelite Specials Ltd.

Cappanargid, Rathangan, Co. Kildare,
Republic of Ireland

Notified body:

OMNI Assured Certification International. Ltd NB 2819

1 Parkgate, Princes Street, Tralee
Co. Kerry, Ireland

Declares in compliance with the Construction Products Regulation (EU) No. 305/2011, that the referred products are manufactured according to the requirements of the European Harmonised Standard EN 845-2:2013 and fulfil the conditions for CE Marking in accordance with annex ZA of EN 845-2:2013

The conformity of the product was determined as per the requirements in Annex ZA of EN 845-2: Specification for ancillary components for masonry - Part 2.

Certificate Number: OMNi-00149-FPC

The AVCP for the product: **System 3**

Essential characteristics

<i>Lintel length</i>	mm	600 1200	1350 1650	1800 2100	2250 2400	2550 2700	2850 3000	3250 3500	3750 4000	4250 4500	4750	EN 845-2: 2013
<i>Safe load bearing capacity</i>	kN	16	16	16	23	23	23	26	26	35	35	
<i>Ultimate load bearing capacity</i>	kN	26	26	26	37	37	37	42	42	56	56	
<i>Deflection under load</i>	Less than effective span / 325 at maximum load											
<i>Mass per meter length</i>	kg/m	17.8										
<i>Water absorption</i>	Zero											
<i>Thermal resistance</i>	50 (steel), 0.036 (insulation) W/mK											
<i>Resistance to fire</i>	NPD											
<i>Durability (corrosion)</i>	Material coating reference L14											
<i>Durability (freeze/thaw)</i>	Resistant											
<i>Dangerous substances</i>	None											

Signed for on behalf of the manufacturer by:

Name: Ryan Marshall

Signature: Ryan Marshall

Date: 10-Oct-19